

# Addressable Sounder FD7204



FD7204 is applicable for sound and LED indication of events registered in Interactive Fire Alarm System IFS7000.

FD7204 is certified on EN54-3. The FD7204 sounder is connected to the signal loop of the IFS7002 panel, through the custom UniTalk protocol.

## Features

---

### LEDs control:

**Duty mode** – flash on a period of 16 sec.;

**Alarm mode** – activated continuous ON;

The flash / activation of the LEDs is programmable from the IFS7002's menus.

## Technical data

---

**Maximum number of sounders in the IFS7002 signal loop:** 25 pcs.

### Voltage:

– 15-30V DC

### Current:

– 6mA on 24 V DC

(LED mode, “without flash” )

Sound level, type “Slow whoop” on 1m: 90dB (A)

Frequency, pattern “Slow whoop”: 0.5 – 1,2 kHz

Temperature: from minus 10°C to 50°C

Dimensions: Ø100, h47mm

Weight: 0.075kg.

Protection: IP 40

Construction: ABS



Office building UniPOS,  
1 Efr. Nikola Paskalev Str., Mladost 1, Sofia 1748, Bulgaria  
Phone: +359 2 97 439 25, +359 2 97 444 69

47 San Stefano Str., Pleven 5800, Bulgaria  
Phone: +359 64 891 100

**[www.unipos-bg.com](http://www.unipos-bg.com)**